

Amendments to the Claims:

Claims 1, 10, 11, 15, 18, 21, 39, 42, 45 and 55-59 have been amended herein. Please note that all claims currently pending and under consideration in the referenced application are shown below. Please enter these claims as amended. This listing of claims will replace all prior versions and listings of claims in the application.

Listing of Claims:

The following is a current listing of the pending claims.

1. (Currently Amended) An apparatus, comprising:
a receiver for receiving a plurality of access requests for transmission on ~~the~~ a shared resource from a respective plurality of remote stations and for measuring the utilization of the shared resource;
a scheduler for allocating a portion of the shared resource to zero or more of the requesting remote stations in response to the plurality of access requests, the allocation comprising zero or one common access grant to a subset of the requesting remote stations and for generating a busy command ~~in response to~~ based at least in part on the measured utilization by other remote stations of the shared resource; and
a transmitter for transmitting the common access grant to the remaining remote stations on one or more common grant channels and for transmitting a busy signal comprising one or more busy commands.

2. (Previously presented) The apparatus of claim 52, wherein:
the scheduler further allocates with an allocation further comprising zero or more individual access grants to zero or more requesting remote stations; and
the transmitter further transmits the individual access grants to the respective remote stations on one or more individual grant channels.

3. (Previously Presented) An apparatus, comprising:
- a receiver for receiving a plurality of access requests for transmission on a shared resource from a respective plurality of remote stations and for measuring the utilization of the shared resource;
 - a scheduler for allocating a portion of the shared resource to zero or more of the requesting remote stations in response to the plurality of access requests, the allocation comprising zero or one common access grant to a subset of the requesting remote stations and for generating a busy command in response to the measured utilization; and
 - a transmitter for transmitting the common access grant to the remaining remote stations on one or more common grant channels and for transmitting a busy signal comprising one or more busy commands;
- the apparatus being further configured to operate with the plurality of remote stations equipped to transmit autonomously on the shared resource, using a limited portion of the shared resource, without an access request or access grant, and wherein:
- the scheduler computes the expected amount of the shared resource to be consumed by the autonomous transmissions and allocates the portion of the shared resource for individual and common access grants in response thereto.

4. (Previously Presented) An apparatus,-comprising:
- a receiver for receiving a plurality of access requests for transmission on a shared resource from a respective plurality of remote stations and for measuring the utilization of the shared resource;
 - a scheduler for allocating a portion of the shared resource to zero or more of the requesting remote stations in response to the plurality of access requests, the allocation comprising zero or one common access grant to a subset of the requesting remote stations and for generating a busy command in response to the measured utilization; and
 - a transmitter for transmitting the common access grant to the remaining remote stations on one or more common grant channels and for transmitting a busy signal comprising one or more busy commands;
- the apparatus being further configured to operate with one or more remote stations transmitting with permission from one or more access grants, the apparatus further comprising:
- a decoder for decoding one or more received packets and determining if the one or more received packets decoded without error; and
- wherein:
- the receiver further receives the one or more packets of data from one or more remote stations, respectively;
 - the transmitter further transmits to the one or more remote stations an acknowledgment and grant extension (ACK-and-Continue) command, respectively, when the respective received packet decoded without error and the access grant for the respective remote station is to be extended; and
 - the scheduler determines the allocation of the portion of the shared resource in accordance with individual and common grants extended with the one or more ACK-and-Continue commands.

5. (Previously presented) The apparatus of claim 52, wherein each busy command comprises one of a first value indicating a decrease or a second value indicating an increase.

6. (Original) The apparatus of claim 5, wherein each busy command alternately further comprises a third value indicating neither an increase or decrease.

7. (Previously presented) The apparatus of claim 52, wherein each busy command comprises one of one or more values indicating respective one or more decreases, the respective decreases indicating different decrease amounts or one or more values indicating respective one or more increases, the respective increases indicating different increase amounts.

8. (Original) The apparatus of claim 7, wherein each busy command alternately further comprises a value indicating neither an increase or decrease.

9. (Canceled)

10. (Currently Amended) A remote station, comprising:
a data buffer for receiving data for transmission;
a message generator for generating an access request message when the data buffer contains data for transmission;
a receiver for receiving one or more common grant channels from a base station and for receiving a busy signal based at least in part on a measured utilization by other remote stations of a shared resource from the base station;
a message decoder for decoding an access grant directed to the remote station, the access grant comprising a common grant on one of the one or more common grant channels; and
a transmitter for transmitting the access request message and for transmitting a portion of data from the data buffer in response to a decoded access grant in accordance with the received busy signal, wherein:
the receiver further receives one or more individual grant channels from the base station;
and
the message decoder further decodes an access grant comprising an individual grant directed on one of the one or more individual grant channels.

11. (Currently Amended) A remote station, comprising:
a data buffer for receiving data for transmission;
a message generator for generating an access request message when the data buffer contains data for transmission;
a receiver for receiving one or more common grant channels from a base station and for receiving a busy signal based at least in part on a measured utilization by other remote stations of a shared resource from the base station;
a message decoder for decoding an access grant directed to the remote station, the access grant comprising a common grant on one of the one or more common grant channels; and
a transmitter for transmitting the access request message and for transmitting a portion of data from the data buffer in response to a decoded access grant in accordance with the received busy signal, wherein the transmitter further transmits a limited portion of the data in the data buffer autonomously, irrespective of whether an access grant has been received, responsive to the received busy signal.

12. (Previously Presented) A remote station, comprising:
a data buffer for receiving data for transmission;
a message generator for generating an access request message when the data buffer contains data for transmission;
a receiver for receiving one or more common grant channels from a base station and for receiving a busy signal from the base station;
a message decoder for decoding an access grant directed to the remote station, the access grant comprising a common grant on one of the one or more common grant channels; and
a transmitter for transmitting the access request message and for transmitting a portion of data from the data buffer in response to a decoded access grant in accordance with the received busy signal, wherein:
the receiver further receives an ACK-and-Continue command; and
the transmitter transmits an additional portion of data from the data buffer in response to a previously decoded access grant, responsive to the received busy signal.

13. (Previously Presented) A remote station, comprising:
a data buffer for receiving data for transmission;
a message generator for generating an access request message when the data buffer contains data for transmission;
a receiver for receiving one or more common grant channels from a base station and for receiving a busy signal from the base station;
a message decoder for decoding an access grant directed to the remote station, the access grant comprising a common grant on one of the one or more common grant channels; and
a transmitter for transmitting the access request message and for transmitting a portion of data from the data buffer in response to a decoded access grant in accordance with the received busy signal, wherein the transmitter further transmits a limited portion of the data in the data buffer autonomously, subsequent to a received ACK, responsive to the received busy signal.

14. (Previously Presented) A remote station, comprising:
a data buffer for receiving data for transmission;
a message generator for generating an access request message when the data buffer contains data for transmission;
a receiver for receiving one or more common grant channels from a base station and for receiving a busy signal from the base station;
a message decoder for decoding an access grant directed to the remote station, the access grant comprising a common grant on one of the one or more common grant channels; and
a transmitter for transmitting the access request message and for transmitting a portion of data from the data buffer in response to a decoded access grant in accordance with the received busy signal, wherein:
the receiver further receives a NAK command; and
the transmitter retransmits the portion of data from the data buffer previously transmitted in response to a previously decoded access grant, responsive to the received busy signal.

15. (Currently Amended) A remote station, comprising:
a data buffer for receiving data for transmission;
a message generator for generating an access request message when the data buffer contains data for transmission;
a receiver for receiving one or more common grant channels from a base station and for receiving a busy signal based at least in part on a measured utilization by other remote stations of a shared resource from the base station;
a message decoder for decoding an access grant directed to the remote station, the access grant comprising a common grant on one of the one or more common grant channels; and
a transmitter for transmitting the access request message and for transmitting a portion of data from the data buffer in response to a decoded access grant in accordance with the received busy signal, wherein the transmission rate is decreased in response to an assertion on the received busy signal.

16. (Original) The remote station of claim 15, wherein the decrease is deterministic.

17. (Original) The remote station of claim 15, wherein the decrease is probabilistic.

18. (Currently Amended) A remote station, comprising:
a data buffer for receiving data for transmission;
a message generator for generating an access request message when the data buffer contains data for transmission;
a receiver for receiving one or more common grant channels from a base station and for receiving a busy signal based at least in part on a measured utilization by other remote stations of a shared resource from the base station;
a message decoder for decoding an access grant directed to the remote station, the access grant comprising a common grant on one of the one or more common grant channels; and
a transmitter for transmitting the access request message and for transmitting a portion of data from the data buffer in response to a decoded access grant in accordance with the

received busy signal, wherein the transmission rate is increased in response to an assertion on the received busy signal.

19. (Original) The remote station of claim 18, wherein the increase is deterministic.

20. (Original) The remote station of claim 18, wherein the increase is probabilistic.

21. (Currently Amended) A remote station, comprising:
a data buffer for receiving data for transmission;
a message generator for generating an access request message when the data buffer contains data for transmission;
a receiver for receiving one or more common grant channels from a base station and for receiving a busy signal based at least in part on a measured utilization by other remote stations of a shared resource from the base station;
a message decoder for decoding an access grant directed to the remote station, the access grant comprising a common grant on one of the one or more common grant channels; and
a transmitter for transmitting the access request message and for transmitting a portion of data from the data buffer in response to a decoded access grant in accordance with the received busy signal, wherein the transmission rate is increased or decreased in response to the received busy signal, the amount of increase or decrease conditioned on a Quality of Service (QoS) service level.

22. (Original) A wireless communication system, comprising:
a plurality of remote stations, each of a subset of which transmit an access request message to form a plurality of access request messages;
a base station for:
receiving the plurality of access request messages;
measuring the utilization of the shared resource;
allocating a shared system resource among the plurality of remote stations;

transmitting zero or more individual access grants to a subset of the requesting remote stations and zero or more common access grants to the remaining requesting remote stations; and
transmitting a busy signal when the measured utilization exceeds a predetermined threshold.

23. (Original) The wireless communication system of claim 22, wherein the requesting remote stations receive the transmitted individual or common access grants and the busy signal and transmit data to the base station respectively in accordance therewith, responsive to the received busy signal.

24. (Original) The wireless communication system of claim 22, wherein a subset of the plurality of remote stations transmit data autonomously, responsive to the transmitted busy signal.

25. (Original) A method of access control of a shared resource, comprising:
receiving a plurality of access requests for transmission on the shared resource from a respective plurality of remote stations;
allocating a portion of the shared resource to zero or more of the requesting remote stations in response to the plurality of access requests, the allocation comprising zero or one common access grant to a subset of the requesting remote stations;
transmitting the common access grant to the remaining remote stations on one or more common grant channels;
measuring the utilization of the shared resource; and
transmitting a busy signal when the measured utilization exceeds a predetermined threshold.

26. (Original) The method of claim 25, wherein:
the allocation further comprises zero or more individual access grants to zero or more requesting remote stations; and

further comprising transmitting the individual access grants to the respective remote stations on one or more individual grant channels.

27. (Original) The method of claim 25, operable with the plurality of remote stations equipped to transmit autonomously on the shared resource, using a limited portion of the shared resource, without an access request or access grant, further comprising:
computing the expected amount of the shared resource to be consumed by the autonomous transmissions and allocating the portion of the shared resource for individual and common access grants in response thereto.

28. (Original) The method of claim 25, operable with one or more remote stations transmitting with permission from one or more access grants, further comprising:
decoding one or more received packets;
determining if the one or more received packets decoded without error;
transmitting to the one or more remote stations an acknowledgment and grant extension (ACK-and-Continue) command, respectively, when the respective received packet decoded without error and the access grant for the respective remote station is to be extended; and
wherein the allocation of the portion of the shared resource is performed in accordance with individual and common grants extended with the one or more ACK-and-Continue commands.

29. (Original) The method of claim 25, wherein the busy signal comprises a series of commands, each command one of a first value indicating a decrease or a second value indicating an increase.

30. (Original) The method of claim 29, wherein the series of commands further comprise a third value indicating neither an increase or decrease.

31. (Original) The method of claim 25, wherein the busy signal comprises a series of commands, each command one of one or more values indicating respective one or more

decreases, the respective decreases indicating different decrease amounts or one or more values indicating respective one or more increases, the respective increases indicating different increase amounts.

32. (Original) The method of claim 31, wherein the series of commands further comprise a value indicating neither an increase or decrease.

33. (Canceled)

34. (Previously Presented) A method of transmission, comprising:
receiving data for transmission;
storing the data in a data buffer;
generating an access request message;
transmitting the access request message;
receiving one or more common grant channels from a base station;
decoding an access grant comprising a common grant on one of the one or more common grant channels;
receiving a busy signal from the base station; and
transmitting a portion of data from the data buffer in response to a decoded access grant adapted in accordance with the received busy signal, further comprising:
receiving one or more individual grant channels; and
wherein the access grant alternately comprises an individual grant directed on one of the one or more individual grant channels.

35. (Previously Presented) A method of transmission, comprising:
receiving data for transmission;
storing the data in a data buffer;
generating an access request message;
transmitting the access request message;
receiving one or more common grant channels from a base station;
decoding an access grant comprising a common grant on one of the one or more common grant channels;
receiving a busy signal from the base station; and
transmitting a portion of data from the data buffer in response to a decoded access grant adapted in accordance with the received busy signal, further comprising transmitting a limited portion of the data in the data buffer autonomously, irrespective of whether an access grant has been received, responsive to the received busy signal.

36. (Previously Presented) A method of transmission, comprising:
receiving data for transmission;
storing the data in a data buffer;
generating an access request message;
transmitting the access request message;
receiving one or more common grant channels from a base station;
decoding an access grant comprising a common grant on one of the one or more common grant channels;
receiving a busy signal from the base station; and
transmitting a portion of data from the data buffer in response to a decoded access grant adapted in accordance with the received busy signal, further comprising:
receiving an ACK-and-Continue command; and
transmitting an additional portion of data from the data buffer in response to a previously decoded access grant adapted to the received busy signal.

37. (Previously Presented) A method of transmission, comprising:
receiving data for transmission;
storing the data in a data buffer;
generating an access request message;
transmitting the access request message;
receiving one or more common grant channels from a base station;
decoding an access grant comprising a common grant on one of the one or more common grant channels;
receiving a busy signal from the base station; and
transmitting a portion of data from the data buffer in response to a decoded access grant adapted in accordance with the received busy signal, further comprising transmitting a limited portion of the data in the data buffer autonomously, subsequent to a received ACK, responsive to the received busy signal

38. (Previously Presented) A method of transmission, comprising:
receiving data for transmission;
storing the data in a data buffer;
generating an access request message;
transmitting the access request message;
receiving one or more common grant channels from a base station;
decoding an access grant comprising a common grant on one of the one or more common grant channels;
receiving a busy signal from the base station; and
transmitting a portion of data from the data buffer in response to a decoded access grant adapted in accordance with the received busy signal, further comprising:
receiving a NAK command; and
retransmitting the portion of data from the data buffer previously transmitted in response to a previously decoded access grant, responsive to the received busy signal.

39. (Currently Amended) A method of transmission, comprising:
receiving data for transmission;
storing the data in a data buffer;
generating an access request message;
transmitting the access request message;
receiving one or more common grant channels from a base station;
decoding an access grant comprising a common grant on one of the one or more common grant channels;
receiving a busy signal from the base station, wherein the busy signal is based at least in part on a measured utilization by other remote stations of a shared resource; and
transmitting a portion of data from the data buffer in response to a decoded access grant adapted in accordance with the received busy signal, wherein the transmission rate is decreased in response to an assertion on the received busy signal.

40. (Original) The method of claim 39, wherein the decrease is deterministic.

41. (Original) The method of claim 39, wherein the decrease is probabilistic.

42. (Currently Amended) A method of transmission, comprising:
receiving data for transmission;
storing the data in a data buffer;
generating an access request message;
transmitting the access request message;
receiving one or more common grant channels from a base station;
decoding an access grant comprising a common grant on one of the one or more common grant channels;
receiving a busy signal from the base station, wherein the busy signal is based at least in part on a measured utilization by other remote stations of a shared resource; and

transmitting a portion of data from the data buffer in response to a decoded access grant adapted in accordance with the received busy signal, wherein the transmission rate is increased in response to an assertion on the received busy signal.

43. (Original) The method of claim 42, wherein the increase is deterministic.

44. (Original) The method of claim 42, wherein the increase is probabilistic.

45. (Currently Amended) A method of transmission, comprising:
receiving data for transmission;
storing the data in a data buffer;
generating an access request message;
transmitting the access request message;
receiving one or more common grant channels from a base station;
decoding an access grant comprising a common grant on one of the one or more common grant channels;
receiving a busy signal from the base station, wherein the busy signal is based at least in part on a measured utilization by other remote stations of a shared resource; and
transmitting a portion of data from the data buffer in response to a decoded access grant adapted in accordance with the received busy signal, wherein the transmission rate is increased or decreased in response to the received busy signal, the amount of increase or decrease conditioned on a Quality of Service (QoS) service level.

46. (Original) An apparatus, comprising:
means for receiving a plurality of access requests for transmission on the shared resource from a respective plurality of remote stations;
means for allocating a portion of the shared resource to zero or more of the requesting remote stations in response to the plurality of access requests, the allocation comprising zero or one common access grant to a subset of the requesting remote stations;

means for transmitting the common access grant to the remaining remote stations on one or more common grant channels;

means for measuring the utilization of the shared resource; and

means for transmitting a busy signal when the measured utilization exceeds a predetermined threshold.

47. (Canceled)

48. (Original) A wireless communication system, comprising:

means for receiving a plurality of access requests for transmission on the shared resource from a respective plurality of remote stations;

means for allocating a portion of the shared resource to zero or more of the requesting remote stations in response to the plurality of access requests, the allocation comprising zero or one common access grant to a subset of the requesting remote stations;

means for transmitting the common access grant to the remaining remote stations on one or more common grant channels;

means for measuring the utilization of the shared resource; and

means for transmitting a busy signal when the measured utilization exceeds a predetermined threshold.

49. (Canceled)

50. (Original) Processor readable media operable to perform the following steps:

receiving a plurality of access requests for transmission on the shared resource from a respective plurality of remote stations;

allocating a portion of the shared resource to zero or more of the requesting remote stations in response to the plurality of access requests, the allocation comprising zero or one common access grant to a subset of the requesting remote stations;

transmitting the common access grant to the remaining remote stations on one or more common grant channels;

measuring the utilization of the shared resource; and
transmitting a busy signal when the measured utilization exceeds a predetermined threshold.

51. (Canceled)

52. (Previously Presented) An apparatus, operable with a plurality of remote stations capable of transmission on a shared resource, comprising:
a receiver for receiving a plurality of access requests for transmission on the shared resource from a respective plurality of remote stations and for measuring the utilization of the shared resource;
a scheduler for allocating a portion of the shared resource to zero or more of the requesting remote stations in response to the plurality of access requests, the allocation comprising zero or one common access grant to a subset of the requesting remote stations and for generating a busy command when the measured utilization exceeds a predetermined threshold; and
a transmitter for transmitting the common access grant to the remaining remote stations on one or more common grant channels and for transmitting a busy signal comprising one or more busy commands.

53. (Previously presented) The apparatus of claim 52, further operable with the plurality of remote stations equipped to transmit autonomously on the shared resource, using a limited portion of the shared resource, without an access request or access grant, and wherein: the scheduler computes the expected amount of the shared resource to be consumed by the autonomous transmissions and allocates the portion of the shared resource for individual and common access grants in response thereto.

54. (Previously presented) The apparatus of claim 52, further operable with one or more remote stations transmitting with permission from one or more access grants, the apparatus further comprising:

a decoder for decoding one or more received packets and determining if the one or more received packets decoded without error; and

wherein:

the receiver further receives the one or more packets of data from one or more remote stations, respectively;

the transmitter further transmits to the one or more remote stations an acknowledgment and grant extension (ACK-and-Continue) command, respectively, when the respective received packet decoded without error and the access grant for the respective remote station is to be extended; and

the scheduler determines the allocation of the portion of the shared resource in accordance with individual and common grants extended with the one or more ACK-and-Continue commands.

55. (Currently Amended) A remote station, comprising:

a data buffer for receiving data for transmission;

a message generator for generating an access request message when the data buffer contains data for transmission;

a receiver for receiving one or more common grant channels from a base station and for receiving a busy signal based at least in part on a measured utilization by other remote stations of a shared resource from the base station;

a message decoder for decoding an access grant directed to the remote station, the access grant comprising a common grant on one of the one or more common grant channels; and

a transmitter for transmitting the access request message and for transmitting a portion of data from the data buffer in response to a decoded access grant in accordance with the received busy signal.

56. (Currently Amended) A method of transmission, comprising:
 receiving data for transmission;
 storing the data in a data buffer;
 generating an access request message;
 transmitting the access request message;
 receiving one or more common grant channels from a base station;
 decoding an access grant comprising a common grant on one of the one or more common grant channels;
 receiving a busy signal based at least in part on a measured utilization by other remote stations of a shared resource from the base station; and
 transmitting a portion of data from the data buffer in response to a decoded access grant adapted in accordance with the received busy signal.

57. (Currently Amended) An apparatus, comprising:
 means for receiving data for transmission;
 means for storing the data in a data buffer;
 means for generating an access request message;
 means for transmitting the access request message;
 means for receiving one or more common grant channels from a base station;
 means for decoding an access grant comprising a common grant on one of the one or more common grant channels;
 means for receiving a busy signal based at least in part on a measured utilization by other remote stations of a shared resource from the base station; and
 means for transmitting a portion of data from the data buffer in response to a decoded access grant adapted in accordance with the received busy signal.

58. (Currently Amended) A wireless communication system, comprising:
means for receiving data for transmission;
means for storing the data in a data buffer;
means for generating an access request message;
means for transmitting the access request message;
means for receiving one or more common grant channels from a base station;
means for decoding an access grant comprising a common grant on one of the one or more
common grant channels;
means for receiving a busy signal based at least in part on a measured utilization by other remote
stations of a shared resource from the base station; and
means for transmitting a portion of data from the data buffer in response to a decoded access
grant adapted in accordance with the received busy signal.

59. (Currently Amended) Processor readable media operable to perform the
following steps:
receiving data for transmission;
storing the data in a data buffer;
generating an access request message;
transmitting the access request message;
receiving one or more common grant channels from a base station;
decoding an access grant comprising a common grant on one of the one or more common grant
channels;
receiving a busy signal based at least in part on a measured utilization by other remote stations of
a shared resource from the base station; and
transmitting a portion of data from the data buffer in response to a decoded access grant adapted
in accordance with the received busy signal.